


FLAMINGO G12R/132D 595-625W



Supreme Quality



High Efficiency

Module efficiency up to 23.1% based on N-Type wafer and TOPCon technology



Excellent Energy Yield

More power output in field operation due to better thermal behaviors, weak-light performance and bifaciality



Anti-degradation

Unsusceptible to LID, LeTID and less annual degradation due to special characteristics of N-Type



Quality Guarantee

High module quality ensures long-term reliability

Module Characteristics

15-Year
Product Warranty

30-Year
Linear Power Warranty

1%
First Year Degradation

0.4%
Annual Power Degradation



At least 87.4% of nominal power up to 30 years



IEC 61215(2021) / IEC 61730(2023)

ISO 9001: 2015: ISO Quality Management System

Anti-PID / Ammonia / Salt-mist / Dust and sand

Made in China

625W

Maximum Power

23.1%

Highest Conversion Efficiency

1%

First Year Degradation


0.4%

2-30 Years Annual Power Attenuation

Mechanical Parameters

Cell Type	N-Type TOPCon
No. of cells	132 (2×66)
Output Cables	TüV 1×4mm ² (+)300mm,(-)200mm in length or customized length
Glass	Front: 2.0mm, AR-coating, semi-tempered Rear: 2.0mm, semi-tempered
Frame	Anodized aluminum alloy frame
Weight	32.4 kg (71.43 lbs)
Dimension	2382×1134×30mm
Packaging	37 pcs per pallet 148 pcs per 20' HC, 740 pcs per 40' HC
Protection Class	Class II
Fire Rating	IEC Class A

Engineering Drawings



* Length:±2mm Width:±2mm Height:±1mm Row Pitch:±2mm

Electrical Characteristics (STC Test)

Module Type	GK-4-66HTBD-595M		GK-4-66HTBD-600M		GK-4-66HTBD-605M		GK-4-66HTBD-610M		GK-4-66HTBD-615M		GK-4-66HTBD-620M		GK-4-66HTBD-625M	
Testing Condition	STC	NOCT	STC	NOCT	STC	NOCT	STC	NOCT	STC	NOCT	STC	NOCT	STC	NOCT
Maximum Power (P _{max} /W)	595	450	600	454	605	458	610	462	615	466	620	469	625	473
Open-circuit Voltage (V _{oc} /V)	47.49	44.96	47.66	45.16	47.83	45.28	48.00	45.49	48.17	45.65	48.34	45.81	48.51	45.97
Short-circuit Current (I _{sc} /A)	15.86	12.80	15.93	12.86	16.00	12.92	16.07	12.96	16.14	13.02	16.21	13.06	16.28	13.12
Maximum Power Voltage (V _{mp} /V)	39.81	37.65	39.95	37.78	40.09	37.91	40.22	38.06	40.35	38.16	40.48	38.31	40.63	38.46
Maximum Power Current (I _{mp} /A)	14.96	11.97	15.03	12.03	15.10	12.08	15.18	12.16	15.25	12.20	15.33	12.27	15.41	12.31
Module Efficiency (%)	22.0		22.2		22.4		22.6		22.8		23.0		23.1	

Note: 1、STC: Irradiance 1000W/M², Cell Temperature 25°C, AM=1.5 2、NOCT: Irradiance 800W/M², Ambient Temperature 20°C, AM=1.5, Wind Speed 1M/S

Different Rearside Power Gain (Reference to 605W)

Rearside Power Gain	5%	10%	20%
Maximum Power at STC (P _{max})	635.3	665.5	726.0
Open-circuit Voltage (V _{oc} /V)	47.8	47.8	47.8
Short-circuit Current (I _{sc} /A)	16.8	17.6	19.2
Maximum Power Voltage (V _{mp} /V)	40.1	40.1	40.1
Maximum Power Current (I _{mp} /A)	15.9	16.6	18.1
Module Efficiency (%)	23.5	24.6	26.9

*The above data is for reference only. When signing a contract, the latest version of the product specification shall prevail.

Temperature Ratings (STC)

Temperature coefficient of I _{sc}	+ 0.045%/°C
Temperature coefficient of V _{oc}	- 0.25%/°C
Temperature coefficient of P _{max}	- 0.29%/°C

Working Parameters

Operating Temperature	-40°C~ +85°C
Power Tolerance	0~ +5W
Maximum System Voltage	1500V(IEC)
NMOT	45±2°C
Maximum Series Fuse Rating	35A
Bifacial Factor	80±5%
Junction Box	IP68

Mechanical Loading

Front Side Maximum Static Loading	5400Pa
Rear Side Maximum Static Loading	2400Pa
Hailstone Test	25mm hailstone at 23m/s

Gokin



Gokin Solar Co., Ltd.

https://www.gokinsolar.com

gk@gokinsolar.com

Office 1102, No. 58 Huajin Street, Hengqin Free Trade Zone, Zhuhai City, Guangdong Province, China.

Product data is updated as of May 2024. Gokin Solar Co., Ltd. reserves the right to change specifications.