

GEM G12R/108S 490-515W



Supreme Quality



High Efficiency

Module efficiency up to 23.2% based on N-Type wafer and TOPCon technology



Excellent Energy Yield

More power output in field operation due to better thermal behaviors, weak-light performance and bifaciality



Anti-degradation

Unsusceptible to LID, LeTID and less annual degradation due to special characteristics of N-Type



Quality Guarantee

High module quality ensures long-term reliability

Module Characteristics

15-Year
Product Warranty

30-Year
Linear Power Warranty

1%
First Year Degradation

0.4%
Annual Power Degradation

515W

Maximum Power

23.2%

Highest Conversion Efficiency

1%

First Year Degradation


0.4%

2-30 Years Annual Power Attenuation

Mechanical Parameters

Cell Type	N-Type TOPCon
No. of cells	108 (2×54)
Output Cables	TÜV 1×4mm ²
	(+)300mm, (-)200mm in length or customized length
Glass	Front: 3.2mm, AR-coating tempered glass
Frame	Anodized aluminum alloy frame
Weight	23.1 kg (50.93 lbs)
Dimension	1961×1134×30mm
Packaging	37 pcs per pallet
	185 pcs per 20' HC, 888 pcs per 40' HC
Protection Class	Class II


Engineering Drawings



* Length:±2mm Width:±2mm Height:±1mm Row Pitch:±2mm

Electrical Characteristics (STC Test)

Module Type	GK-4-54HT-490M		GK-4-54HT-495M		GK-4-54HT-500M		GK-4-54HT-505M		GK-4-54HT-510M		GK-4-54HT-515M	
Testing Condition	STC	NOCT	STC	NOCT	STC	NOCT	STC	NOCT	STC	NOCT	STC	NOCT
Maximum Power (Pmax/W)	490	371	495	375	500	379	505	383	510	386	515	390
Open-circuit Voltage (Voc/V)	39.61	36.84	39.81	37.02	40.02	37.22	40.22	37.40	40.42	37.59	40.62	37.78
Short-circuit Current (Isc/A)	15.74	12.91	15.81	12.96	15.88	13.02	15.95	13.08	16.02	13.14	16.08	13.19
Maximum Power Voltage (Vmp/V)	32.65	30.30	32.85	30.48	33.05	30.67	33.25	30.86	33.45	31.04	33.64	31.22
Maximum Power Current (Imp/A)	15.01	12.25	15.07	12.30	15.13	12.35	15.19	12.40	15.25	12.44	15.31	12.49
Module Efficiency (%)	22.0		22.3		22.5		22.7		22.9		23.2	

Note: 1. STC: Irradiance 1000W/M², Cell Temperature 25°C, AM=1.52. NOCT: Irradiance 800W/M², Ambient Temperature 20°C, AM=1.5, Wind Speed 1M/S

Temperature Ratings (STC)

Temperature coefficient of Isc	+ 0.045%/°C
Temperature coefficient of Voc	- 0.25%/°C
Temperature coefficient of Pmax	- 0.29%/°C

Working Parameters

Operating Temperature	-40°C~ +85°C
Power Tolerance	0~ +5W
Maximum System Voltage	1500V(IEC)
NOCT	45±2°C
Maximum Series Fuse Rating	30A
Junction Box	IP68

Mechanical Loading

Front Side Maximum Static Loading	5400Pa
Rear Side Maximum Static Loading	2400Pa
Hailstone Test	25mm hailstone at 23m/s

Gokin



Gokin Solar Co., Ltd.

<https://www.gokinsolar.com>
gk@gokinsolar.com

Office 1102, No. 58 Huajin Street, Hengqin Free Trade Zone, Zhuhai City, Guangdong Province, China.

Product data is updated as of May 2024. Gokin Solar Co., Ltd. reserves the right to change specifications.